AGP-6800 Series

Exit Pay Station

Features:

- Unattended exit payment system calculates variable rate or flat rate fees utilizing mag-stripe technology.
- Provides an economical method to offer additional payment locations in the exit lanes of a facility.
- · Includes a lighted patron guidance system and easy to read touch screen display.
- Electronic shutter system protects the ticket slot, coin slot, and note slot; activated open by the start of a transaction.
- · Accepts entry tickets, exit tickets processed at a central pay location; cancelled tickets, lost tickets, validation coupons and service tickets.



SPECIFICATIONS

AGP-6800 Exit Pay Station

Electrical:

- Power source: 110 120 VAC, 50/60 Hz
 Power consumption: 11.5 amps with heater
- Power reserve: Clock and program data are protected

for 3 years by Li battery

Ambient Environment:

- Temperature: -12° F to 120° F (-25° C to 50° C)
- Relative humidity: 20% to 90% (no water condensation)
- · Automatic thermostat-controlled heater and fan

Housing:

 Height:
 57.2" (1453 mm)

 Width:
 29.53" (750 mm)

 Depth:
 17.72" (445 mm)

 Construction:
 Sheet steel housing

Finish: Textured Powder coat finish RAL 9010
Weight: Approximately 443 lb. (201 kg)

Time Control:

- Quartz oscillated, accurate within ±3 seconds per week at 68° F to 86° F (20° C to 30° C)
- · Programmable Daylight Savings Time adjustment

Off-Line Operation:

AGP-6800 operates as a stand-alone lag-time reader.

On-Line Operation:

Utilizes RS-485 communication with the parking management software host. Data sent from the pay station to the Host PC includes individual transaction data and alarm and event messages. Data sent from the parking management software to pay station includes time synchronization and backout ticket data.

Security:

Multi-point safety lock system with concealed hinges **Voice Guides:** Payment, fee, receipts and reports.

Accepted Coins: U.S. \$.05, .10, .25, 1.00

Four Recycling


Coin Hoppers: U.S. \$.05, .10, .25, 1.00

Note Reader: Four-way note reader accepts U.S. \$1.00, 5.00, 10.00, 20.00

Vaults: Coin vault collects overflow coins; Bank note vault stores

collected notes.

Printer: Thermal printer is used to print receipts and total reports.



Specifications are approximate and are subject to change without notice

REPRESENTED BY:



Corporate Headquarters: 140 Harrison Avenue, Roseland, NJ 07068-1239 (973) 403-1900 www.amano.com